

Fixed Flat Rooflight

Product Information

- Thermally broken aluminium comprising of 2 x 27mm polyamide inserts
- 48mm overhang for a better weather tight seal
- Glass from 1.0 U value to 0.2
- Available in Double Glazed or Triple Glazed
- Solar Control Self Cleaning Glass included as a standard
- No External Fixings



Testing

- Weathertightness in accordance with BS 6375-1:2015
- Air Permeability test in accordance with BS EN 1026:2000
- Watertightness test in accordance with BS EN 1027:2000
- Resistance to wind load in accordance with BS EN 12211:2000

Lead Time

Standard Specification: 14-16 working days

Heat Soaking: 3-4 weeks

Toughened Laminate: 4 weeks

Installation

To ensure a better weathertightness, there are no external fixings on our Flat Rooflights.

Our Flat Rooflight will be supplied with metal fixings straps which are screwed into the internal timber upstand and then covered over with plasterboard to ensure the perfect frameless look.

Minimum pitch: 5 degrees

Maximum pitch: 45 degrees

Full fitting guides will be supplied with every Rooflight and are available to download from our website.

Colours

Standard Colours:

Anthracite Grey RAL 7016m

Jet Black RAL 9005m

Dual colour (white internal) also available for an additional charge.

Bespoke RAL colour also available for an additional charge.

Warranty

Our Rooflights are guaranteed for 5 year parts only in accordance to our terms and conditions.

Both warranty certificate and our terms & conditions are available to download from our website.

Manual Opening (with winder)

Product Information

- Thermally Broken Aluminium
- 4 x 35mm Polyamide inserts
- Triple Seal Gasket System
- Solar Control Self Cleansing Glass included as a standard
- Double Glazed
- 300mm Opening
- Chrome winder with 2m extension pole
- Maximum size 1200 x 1200mm with a single winder
- Tandem winder also available in larger applications



Testing

- Weathertightness in accordance with BS 6375-1:2015
- Air Permeability test in accordance with BS EN 1026:2000
- Watertightness test in accordance with BS EN 1027:2000
- Resistance to wind load in accordance with BS EN 12211:2000

Lead Time

Standard Specification: 14-16 working days

Heat Soaking: 3-4 weeks

Toughened Laminate: 4 weeks

Installation

To ensure a better weathertightness, there are no external fixings on our Manual Opening Rooflight.

Minimum pitch: 5 degrees

Maximum pitch: 15 degrees

Full fitting guides will be supplied with every Rooflight and are also available to download from our website.

Colours

Standard Colours:

Slate Grey RAL 7015m

Anthracite Grey RAL 7016m

Jet Black RAL 9005m

Dual colour (white internal) also available for an additional charge.

Bespoke RAL colour also available for an additional charge.

Warranty

Our Rooflights are guaranteed for 5 year parts only in accordance to our terms and conditions.

Both warranty certificate and our terms & conditions are available to download from our website.

Electric Opening Rooflight

Product Information

- Thermally Broken Aluminium
- 4 x 35mm Polyamide inserts
- Triple Seal Gasket System
- Solar Control Self Cleaning Glass included as a standard
- 250mm Opening
- Wireless Remote Control included as a standard
- Motor quantity size dependant
- Additional sensors available
- Maximum size 1500 x 3200mm (Triple Motor System)



Testing

- Weathertightness in accordance with BS 6375-1:2015
- Air Permeability test in accordance with BS EN 1026:2000
- Watertightness test in accordance with BS EN 1027:2000
- Resistance to wind load in accordance with BS EN 12211:2000

Lead Time

Standard Specification: 3 weeks

Heat Soaking or Toughened Laminate: 3-4 weeks

Installation

To ensure a better weathertightness, there are no external fixings on our Electric Opening Rooflight.

Minimum pitch: 5 degrees

Maximum pitch: 15 degrees

Full fitting guides will be supplied with every Rooflight and are also available to download from our website.

Colours

Standard Colours:

Slate Grey RAL 7015m

Anthracite Grey RAL 7016m

Jet Black RAL 9005m

Dual colour (white internal) also available for an additional charge.

Bespoke RAL colour also available for an additional charge.

Warranty

Our Rooflights are guaranteed for 5 year parts only in accordance to our terms and conditions.

Both warranty certificate and our terms & conditions are available to download from our website.